

Coil Specification (at 20 °C):

Coil Sensitivity	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance ($\Omega \pm 10\%$)	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Maximum Allowable Voltage (VDC)
GM4-L	3	50.0	60	0.15	70% Maximum	5% Minimum	150%
	5	30.0	167				
	6	25.0	240				
	9	16.7	540				
	12	12.5	960				
GM4-T	3	66.7	45	0.2		10% Minimum	
	5	40.0	125				
	6	33.3	180				
	9	22.2	405				
	12	16.7	720				
	18	11.1	1,620				
	24	8.3	2,880				
GM4-D	48	4.2	11,520	0.3	66.7% Maximum		
	5	89.3	56	0.45			
	6	75.0	80				
	9	50.0	180				
	12	37.5	320				
	18	25.0	720				
	24	18.8	1,280				
	48	9.6	5,000				

Ordering Information:

GM4 - SH - 2 12 L W

Contact Material :

Nil: AgPd(Gold clad)
W: AgNi(Gold clad)

Coil Power:

L: 0.15W
T: 0.2W
D: 0.45W

Coil Voltage:

03, 05, 06, 09, 12, 18, 24, 48

Number of Pole:

2: Two Poles

Type of Sealing:





SH: Sealed Type

Item:

GM4

Dimension:

GM4



BOTTOM VIEW

BOTTOM VIEW

